



ACOS GRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



AKORN 3M + ASP



The AKORN 3M + ASP is a drying tunnel suitable to dry the inks printed in DIRECT TO GARMENT (DTG). The AKORN 3M + ASP is equipped with hot air turbine that will work in close loop air circuit so you have maximum drying capacity when working in the drying process from DIRECT TO GARMENT (DTG) inks. The AKORN 3M+ ASP is a drying tunnel 100% hot air.

Note: As características podem ser alteradas sem aviso prévio



**ACOS
GRAF**
FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

Rua do Castalhão - Canelas (Zona Industrial da Mina), nº320 4410 - 269 Canelas
VNG - Portugal P.O.Box - 45 -4408 VALADARES CODEX - Portugal
Tel. +351 227 621 679 / +351 227 621 901 - Fax +351 227 623 375
www.acosgraf.com | geral@acosgraf.com

Mesh belt coated with TEFLON;

Electronic speed adjuster from belt speed;

www.acosgraf.com

Re circulation from air in closed loop circuit for option water base drying, PLASTISOL and others;

Hot air velocity with the possibility from adjustment;

Heating emitters in chromium nickel;

Digital temperature controller with PID method;

Thermal isolation made by 10 mm thickness material from hot chamber;

Chimney to make smoke exhaustion;

Maximum height from object that you can dry is 13 cm as standard;

Maximum working temperature as standard - 180 °c;

Other dimensions can be manufacture by request.

Equipped as standard with a smoke extraction system that includes a chimney at the entrance and exit + a

suction motor for smoke extraction

AKORN 3M + ASP	Uni	AK ASP 30007	AK ASP 30008	AK ASP 30010	AK ASP 30012	AK ASP 30015	AK ASP 30016
Heating dimension	Cm	300x70	300x80	300x100	300x120	300x150	300x160
Curing time range	seg.	60 - 360	60 - 360	60 - 360	60 - 360	60 - 360	60 - 360
Width from belt	Cm	70	80	100	120	150	160
Maximum height from objects to dry	Cm	13	13	13	13	13	13
Power install	kW	19	21	27	32	40	42
Max. working temperature	°C	180	180	180	180	180	180
External length	Cm	550	550	550	550	550	550
External width	Cm	115	125	145	165	185	195
External height	Cm	170	170	170	170	170	170
Weight	Kg	450	490	540	600	650	670
Voltage	V	3x400	3x400	3x400	3x400	3x400	3x400

Note: As características podem ser alteradas sem aviso prévio