



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



UV DRYER 2X LAMP + CROSS OVER + COLD



The machine UVDRYER 2xLAMP + CROSS OVER + COLD is a drying tunnel suitable to dry UV inks. The UVDRYER 2xLAMP + CROSS OVER + COLD is equipped with two UV high performance lamps able to dry the hardest job printed with UV ink. The LAMP UVDRYER 2xLAMPS + + CROSS OVER + COLD is fitted with CROSS OVER on the entry + 1 meter of ambient air pulsating after UV lamps.

www.acosgraf.com

Note: As características podem ser alteradas sem aviso prévio




ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



Equipped with 2x high performance UV lamps



"CROSS OVER" equipped with pneumatic cylinders to control UP/DOWN



3xIR lamp box with power adjustment between 20% to 100%

Control panel with 7 inches touch screen

PRODUCT DESCRIPTION

- Equipped with 2x high performance UV lamps;
- Electronic transformer for adjusting the UV lamp power from 20% to 100%;
- Air ambient pulsating after passing trough UV lamps to lower sheet temperature;
- UV lamp cocoon closed below by quartz crystals to prevent heat from passing through the material;
- Cassette-type UV lamp system for easy assistance, lamp removal and cleaning;
- Anti-static Teflon mesh belt;
- Electronic belt speed variator;
- High performance fan for cooling the UV lamp;
- 7-inch touch screen for UV lamp control with indicadores of service menus that includes several information to have a correct UV lamp operation;
- Digital indicator of actual belt speed for easy operator adjustment;
- Vacuum to hold sheet down in the entire UV tunnel area;
- "CROSS OVER" at the tunnel entrance equipped with vacuum and up / down through pneumatic cylinders;

UV DRYER 2x Lamp + Cross Over + Cold	Uni	UVDR 2x90 + Cross + 1M	UVDR 2x110 + Cross + 1M
UV lamp lenght	Cm	90	110
Maximum UV curing width	Cm	80	100
Belt width	Cm	90	110
Total power install in UV lamp	kW	2* 10,8	2* 13,2
Cooling lenght	Cm	100	100
CROSS OVER lenght	Cm	72	72
Total power install	Kw	25	30
Voltage	V	3x 400	3x 400

Note: As características podem ser alteradas sem aviso prévio

www.acosgraf.com