



ACOS GRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



AIRDRYER 3M



www.acosgraf.com

The AIRDRYER 3M is a drying tunnel suitable to dry plastisol inks; water base or solvent inks. The AIRDRYER 3M is equipped with "a" hot air turbine that will work in a close loop air circuit for maximum drying capacity for water base and other types of ink

Note: As características podem ser alteradas sem aviso prévio



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



Turbina de re circulação de ar quente de alto rendimento dando a possibilidade de secar tintas base de água e outras



Opção de painel electrónico com opção de economização de energia



Possibilidade de equipar tunel com 2 tapetes individuais



Pontes de ar frio para arrefecer peça disponíveis



Opção de abertura lateral feita através de cilindros disponíveis



Ajuste de tapete automático em opção

PRODUCT DESCRIPTION

- Mesh belt coated with TEFLON;
- Electronic speed adjuster for belt speed;
- Re-circulation of air in closed circuit for option water base drying;
- Hot air velocity with the possibility for adjustment;
- Heating emitters in chromium nickel;
- Digital temperature controller with PID method;
- Extraction of vapors (steam - condensation);
- Maximum height of object that you can dry is 13 cm as standard;
- Maximum working temperature as standard - 180 °c.

AIRDRYER 3M	Units	AI 30007	AI 30008	AI 30010	AI 30012
Heating dimension	Cm	300x70	300x80	300x100	300x120
Curing time range	s	60 - 180	60 - 180	60 - 180	60 - 180
Width of belt	Cm	70	80	100	120
Maximum height of objects to dry	Cm	13	13	13	13
Power install	kW	18,5	22	27	32
Maximum working temperature	C	200	200	200	200
External length	Cm	415	415	415	415
External width	Cm	115	125	145	165
External height	Cm	130	130	130	130
Weight	Kg	350	470	500	530
Voltage	V	380	380	380	380

Note: As características podem ser alteradas sem aviso prévio