



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



TEXBLACK



www.acosgraf.com

The TEXBLACK is a machine designed to cure after each screen printing process (colour). The TEXBLACK can be used with any type from automatic carousel printing machine. The TEXBLACK can be equipped with several types of START signals such as: photocell, foot pedal or machine control.

Note: As características podem ser alteradas sem aviso prévio



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com




Equipado com 3 zonas de calor de acionamento individual, ajuste de potência para uma melhor rentabilidade energética



Cilindros pneumáticos para baixar e levantar o painel negro iniciando a temporização de tempo de secagem automaticamente



Possibilidade de rodar o flash 90 graus para uma melhor utilização das zonas de calor sem desperdício de energia



Secador 100% sem emissão de luz para grandes áreas de secagem



Outros tipos de flash com diversas formas disponíveis



Flash com carros de transporte para máquinas MHM disponíveis

PRODUCT DESCRIPTION

Equipped with high performance black panel heat source;
Black panel divided into 3 heating zones with individual ON/ OFF to achieve the highest energy saving ;
Possibility to adjust power output between 20% to 100%;
START order can be received from automatic machine and be machine controlled;
Pneumatic cylinders to raise and lower the black panel with automatic START from timer that controls curing cycle;
End signal of machine from time from curing can be communicated to machine;
Security timer to avoid over curing or damage the pallets;
Possibility to turn black panel 90 degrees to achieve the optimal curing result with low power consumption;
Can be equipped with photocell read movement of pallet or foot pedal to be used in manual machines.

TEXBLACK	Units	TB 0704	TB 0710
Flash curing area	Cm	70x46	70x100
Flash curing time	S	0 to 30	0 to 30
Height from working platform	cm	85 a 120	85 a 120
Power Output	W	4400	9591
Weight	Kg	150	200
Voltage	V	230 or 400	230 or 400

Note: As características podem ser alteradas sem aviso prévio