



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



TEXFLASH



www.acosgraf.com

The TEXFLASH is a machine designed to cure after each screen printing process (colour). The TEXFLASH can be used with an automatic or manual textile printing machine.

Note: As características podem ser alteradas sem aviso prévio



ACOSGRAF

FÁBRICA DE MÁQUINAS GRÁFICAS, LDA.

www.acosgraf.com



PRODUCT DESCRIPTION

- Heat Source can be : 6000W; 9000W or 13500W;
- Ventilation fans to harmonize drying process;
- Automatic or manual set up available;
- Possibility to adjust flashing time;
- Possibility to adjust power output of the lamp between 20 to 100%;
- Each lamp with independent ON/OFF switch;
- Option to have start made by: photocell; limit switch; by machine control or footpedal;
- Available to have the flash cure making machine communication control with: SROQUE; MHM; Hebbecker; Walz; etc...
- Preheating of lamps between cycles as standard;
- Quick and easy replacement from lamps.

TEXFLASH	Units	TF 6000	TF 9000	TF 13500
Flash curing area	Cm	59x40	59x40	70 x 50
Height from working platform	cm	85 a 120	85 a 120	85 a 120
External depth	cm	101	101	65
External width	Cm	52	52	64
External height	Cm	104 a140	104 a140	104 a140
Power install	Kw	6000	9000	13500
Weight	Kg	40	45	
Voltage	V	3x 230 ou 3x 400	3x 230 ou 3x 400	3x 230 or 3x 400
Shipping dimensions (W*D*H)	Cm	101*52*105	101*52*105	
Shipping dimensions 3 units (W*D*H)	Cm	120*100*196	120*100*196	

Note: As características podem ser alteradas sem aviso prévio

www.acosgraf.com